

BEST AVAILABLE COPY

Application No. 09/852,033
 Docket No. 031884-1000
 Page 3

AMENDMENT TO THE CLAIMS

The following set of claims is presented in accordance with 37 C.F.R. 1.121 and by making this submission any claim not indicated as currently amended is asserted not to be changed relative to the immediate prior version of the claim. Please amend the claims as follows:

1. (Currently Amended) A user interface operable to create, on a display device, a window for displaying a plurality of menu editor items for user selection, said menu editor items comprising:

a sequence editor item for creating a RF pulse sequence from at least one value; and

a sequence tailor editor item for user interaction with a graphical representation of a selected pulse sequence, wherein during said user interaction, the selected pulse sequence is graphically displayed to the user,

~~wherein~~ said user interaction includes including dynamic, non-standard and on-the-fly manipulation of, and modification to, said graphical representation of said selected pulse sequence [, and]] that is currently undergoing user interaction with real time visual feedback of the interaction to the user of on the manipulated pulse sequence to the user, and

wherein said menu editor items further comprise a scan setting menu editor item for initiation of a magnetic resonance imaging scan.

2. (Original) The user interface in accordance with claim 1, wherein said sequence tailor editor item is activated in response to user selection.

3. (Original) The user interface in accordance with claim 1, wherein user selection of said sequence editor item activates a display of at least one sequence parameter for creating said pulse sequence, said at least one sequence parameter being operable to accept a default value.

4. (Original) The user interface in accordance with claim 3, wherein said at least one sequence parameter is operable to accept a user entered value.

NVA304680.1

Application No. 09/852,033

Docket No. 031884-1000

Page 4

5. (Original) The user interface in accordance with claim 3, wherein said at least one sequence parameter is selected from the group consisting of: a gradient resolution parameter, a radio frequency pulse resolution parameter, a echo gathering time parameter, a sequence name parameter, at least one gradient motion compensation parameter, at least one radio frequency pulse characteristic parameter, and at least one data acquisition parameter.

6. (Original) The user interface in accordance with claim 3, wherein acceptance, by the user interface, of the at least one sequence parameter activates said sequence tailor editor item.

7. (Original) The user interface in accordance with claim 1, wherein activation of said sequence tailor editor item activates display of said pulse sequence and at least one control feature.

8. (Original) The user interface in accordance with claim 7, wherein said at least one control feature comprises at least one of a control section, a shape editor, a block editor, and a time scaler.

9. (Original) The user interface in accordance with claim 8, wherein said shape editor, when activated, is operable to modify at least one radio frequency pulse characteristic parameter and the radio frequency pulse shape associated with said selected pulse sequence.

10. (Original) The user interface in accordance with claim 8, wherein said time scaler, when activated, displays at least one vertical line through the graphically displayed selected pulse sequence for assisting the user in analysis of timing relations of the pulse sequence.

11. (Original) The user interface in accordance with claim 1, wherein said graphical representation within said window on said display device is divided into a plurality of portions.

NVA304680.1

Application No. 09/852,033

Docket No. 031884-1000

Page 5

12. (Original) The user interface in accordance with claim 11, wherein said plurality of portions comprises at least one of a radio frequency pulse characteristics graph, a slice select gradient graph, a signal acquisition graph, and a phase encoding graph.

13. (Canceled).

14. (Original) The user interface in accordance with claim 13, wherein selection of said scan setting menu editor item displays at least one type of scan to perform.

15. (Original) The user interface in accordance with claim 14, wherein said at least one type of scan comprises at least one scan selected from the group consisting of: a two dimensional scan, a combination scan, a three dimensional scan, a three dimensional combination scan, a two dimensional fast spin echo scan, and combinations thereof.

16. (Original) The user interface in accordance with claim 14, wherein said type of scan, when activated, displays at least one setting imaging parameter, said setting imaging parameter being operable to accept at least one default value.

17. (Original) The user interface in accordance with claim 16, wherein said at least one setting imaging parameter is operable to accept at least one user-entered value.

18. (Original) The user interface in accordance with claim 16, wherein said at least one setting imaging parameter is selected from the group consisting of: a number of slices parameter, a slice thickness parameter, a sequence repetition parameter, a number of phase encoding levels parameter, a discrete Fourier transform size parameter, a polarity flipping parameter, and combinations thereof.

19. (Currently Amended) A method for creation and customization of pulse sequences, said method comprising the steps of:

creating a window on a display device for displaying a plurality of menu editor items for user selection;

displaying a sequence editor item for creating a RF pulse sequence from at least one of user-entered values and default values;

NVA304680.1

Application No. 09/852,033

Docket No. 031884-1000

Page 6

displaying a sequence tailor editor item for user interaction with a graphical representation of a selected pulse sequence; and

displaying, graphically, said pulse sequence to the user,

wherein said user interaction includes including dynamic, non-standard and on-the-fly manipulation of, and modification to, said graphical representation of said selected pulse sequence that is currently undergoing user interaction with real time visual feedback of the interaction to the user of on the manipulated pulse sequence to the user, and

wherein said method further comprising the steps of:

initiating a magnetic resonance imaging scan by activating a scan setting menu editor item within said window on said display device; and
displaying at least one setting imaging parameter.

20. (Original) The method in accordance with claim 19, wherein said creating step further comprises the step of:

displaying a scan setting menu editor item for initiation of a magnetic resonance imaging scan.

21. (Original) The method in accordance with claim 20, wherein, upon initiation of said magnetic resonance imaging scan, said method further comprises the step of:

initiating at least one of a two dimensional scan, a two dimensional combination scan, a three dimensional scan, a three dimensional combination scan, and a two dimensional fast spin echo scan.

22. (Original) The method in accordance with claim 19, further comprising the step of:

dividing said graphical representation within said window on said display device into a plurality of portions.

23. (Original) The method in accordance with claim 22, wherein said step of dividing further comprises the step of dividing said graphical representation into at least one of a radio frequency pulse characteristics graph, a slice select gradient graph, a signal acquisition graph, and a phase encoding graph.

NVA304680.1

Application No. 09/852,033

Docket No.: 031884-1000

Page 7

24. (Canceled).

25. (Original) The method in accordance with claim 19, said method further comprising the steps of:

displaying, in response to selection of said sequence editor item, at least one sequence parameter for creating said pulse sequence; and

accepting, by said at least one sequence parameter, at least one of said default values.

26. (Original) The method in accordance with claim 25, wherein said step of accepting further comprises the step of:

accepting, by said at least one sequence parameter, at least one of said user-entered values.

27. (Original) The method in accordance with claim 26, wherein said step of displaying said at least one sequence parameter further comprises the step of:

displaying at least one additional parameter, said additional parameter selected from the group consisting of:

a gradient resolution parameter, a radio frequency pulse resolution parameter, an echo gathering time parameter, a sequence name parameter, a plurality of gradient motion compensation parameters, a plurality of radio frequency pulse parameters, and a plurality of data acquisition parameters.

28. (Original) The method in accordance with claim 26, said method further comprising the step of:

activating said sequence tailor editor item by at least one of user selection and a response to said step of accepting of said at least one sequence parameter by a user interface.

29. (Original) The method in accordance with claim 28, said method further comprising the step of:

displaying the selected one of said pulse sequences and at least one control feature for at least one of plot modification and plot enhancement.

30. (Original) The method in accordance with claim 29, wherein said step of displaying further comprises the step of:

NVA304680.1

Application No. 09/852,033
Docket No. 031884-1000
Page 8

displaying at least one of a control section, a shape editor, a block editor, and a time scaler.

31. (Original) The method in accordance with claim 30, wherein said step of displaying at least one of a control section, a shape editor, a block editor, and a time scaler further comprises the steps of:

activating said shape editor; and

modifying at least one of the radio frequency pulse characteristic parameters and the radio frequency pulse shape associated with said pulse sequence.

32. (Original) The method in accordance with claim 30, wherein said step of displaying at least one of a control section, a shape editor, a block editor, and a time scaler further comprises the steps of:

activating said time scaler; and

displaying at least one vertical line through the graphically displayed pulse sequence for assisting the user in analysis of timing relations of the pulse sequence.

33. (Original) The method in accordance with claim 30, wherein said step of displaying further comprises the step of:

displaying at least one of a number of slices parameter, a slice thickness parameter, a sequence repetition parameter, a number of phase encoding levels parameter, a discrete Fourier transform size parameter, and a polarity flipping parameter.

34 - 70. (Canceled)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.